

CAT. 6A U/FTP 28AWG, 500MHz, LSZH, RIBBON X 4

PGS-FL6A8-24ST342X1

STANDARD COMPLIANCE


ANSI/TIA-568-C.2 CATEGORY 6A: PATCH CABLE

IEC60332-1-2 FLAME TEST

RoHS COMPLIANCE FOR THE REQUIREMENT OF EUROPEAN UNION ISSUED DIRECTIVE 2011/65/EU



SECTION PLANS



CONSTRUCTION

		CATEGORY 6A U/FTP STRANDED
CONDUCTOR	MATERIAL & SIZE	BARE COPPER, 28AWG
	DIAMETER	7/0.12mm +/-0.003mm
INSULATION	MATERIAL	HDPE(CMI-75E)
	THICKNESS	MIN. AVERAGE THICKNESS: 0.28mm MIN.THICKNESS: 0.22mm
	COLOR CODE	Pair 1: Blue & White/Blue Pair 3: Green & White/Green Pair 2: Orange & White/Orange Pair 4: Brown & White/Brown
	DIAMETER	0.9 +/-0.03mm
	TENSILE STRENGTH	16.5 MPa / 2400 PSI
	ULTIMATE ELONGATION	≥300%
JACKET	MATERIAL	CMX-LSHF Compound
	THICKNESS	MIN. AVERAGE THICKNESS: 0.585mm MIN.THICKNESS: 0.485mm
	OVERALL DIAMETER	5.0mm +/-0.3mm X 4C
	MINIMUM BENDING RADIUS	≥ 8 TIMES OF OVERALL DIAMETER
	MAXIMUM PULLING TENSION	MAX. 85N
	TENSILE STRENGTH	8.3 MPa / 1200 PSI
	ULTIMATE ELONGATION	≥100%
SHIELDING	MATERIAL	Aluminum & Mylar Tape
DRAIN WIRE	MATERIAL	Tinned Copper

ELECTRIC REQUIREMENT

		CATEGORY 6A U/FTP STRANDED
CHARACTERISTIC IMPEDENCE(Zo)		85 ~ 115Ω (1 ~ 500MHz)
DC. RESISTANCE CAPACITANCE UNBALANCE		5%
PAIR-TO-GROUND CAPACITANCE UNBALANCE		330 pF/100M MAX.
CONDUCTOR RESISTANCE		22.3Ω/ 100M 20°C MAX.
MUTUAL CAPACITANCE		5600 pF/100M MAX.
SPARK TEST		2.5KV
NOMINAL VELOCITY OF PROPAGATION (N.V.P.)		80%

CAT. 6A U/FTP 28AWG, 500MHz, LSZH, RIBBON X 4

PGS-FL6A8-24ST342X1

ENVIRONMENTAL CONDITION & USAGE

TEMPERATURE RANGE	SHIPPING & STORAGE	-20°C to 75°C
	INSTALLATION	0°C to 50°C
	OPERATION	-10°C to 60°C

TRANSMISSION REQUIREMENTS

FREQUENCY (MHz)	MAX. ATTENUATION (dB/100m)	MIN, Pr-Pr NEXT (dB)	MIN. PSNEXT (dB)	MIN. RETURN LOSS (dB)
1	6.0	74.3	72.3	20.0
8	11.1	60.8	58.8	24.5
16	20.8	56.2	54.2	25.0
25	28.5	53.3	51.3	24.3
100	55.4	44.3	42.3	19.0
250	65.1	38.3	36.3	15.6
400	75.6	35.3	33.3	13.8
500	85.4	33.8	31.8	13.0

Values show on tables above are for reference purpose only.

MARKING & PACKAGING

PACKAGING	FT/ BOX	FT/ BOX
APPROX. WEIGHT(kg)		
DIMENSION(mm)		
PACKAGES per PALLET		
MARKING	4PR 28AWG PATCH CABLE 75°C ISO/IEC 11801 Category 6A 10G U/FTP LSZH PT pactech FlexLite Ribbon PGS-FL6A8-24ST342X1 STRANDED BATCH NO. RoHS	